



Technical Data - BOK Heavy Duty Fitness System HD32G40

Nb. System design will be dependent on equipment loadings / demands and finished floor level required. Please call to discuss project requirements.

System Components

- a. Gypsum Particle Technology Board (GPT Board)
600mm x 600mm x 32mm – 1500kg/m³
- b. 40mm x 40mm BOK-BAT heavy duty composite battens (2.4m Lengths)
- c. 45mm PU SBR crumb/ shred pre-formed Cradle feet
- d. 2mm, 5mm, 10mm packers for levelling adjustment, 30mm base packers
- e. Perimeter dampener strips sbr/foam
- f. Single Part PU Adhesive (Approx 1 Litre per 36sqm)
- g. Final Finished Floor Height: 92.0 mm – 131.0mm

Substrates

Screeds required to be fully cured before installation. Use damp proof membrane (such as 1200 gauge polythene sheet) over ground floor slabs and new concrete bases above ground.

Pricing & Ordering

Prices are based per system pre-designed specifically on a project basis and design allows for a 5% wastage factor. We therefore need only the dimensions of the space to provide all the components required. For larger gyms, small adjoining rooms or irregular shaped areas additional materials will be required, therefore the sqm price should be treated as a guide only, these additional components will require separate calculation and pricing.

Sport & Fitness Flooring
Wyastone Business Park
Wyastone Leys
Monmouth
NP25 3SR
T: 01600 887521
E: info@sportandfitnessflooring.com

Lead Times

6 – 8 Weeks

