



## **Technical Data - BOK Standard Fitness System FS22P25**

Nb. System design will be dependent on equipment loadings / demands and finished floor level required. Please call to discuss project requirements.

### **System Components**

- a. 22mm Ply 2400mm x 1200mm x 22mm
- b. 43mm x 25mm Treated Kiln Dried Softwood Battens (1.8m Lengths)
- c. 40mm PU SBR crumb/ shred pre-formed Cradle feet
- d. 2mm, 5mm, 10mm packers for levelling adjustment, 30mm base packers
- e. Perimeter dampener strips sbr/foam
- f. Single Part PU Adhesive (Approx 1 Litre per 36sqm)
- g. Final Finished Floor Height: 67.0 mm - 106.0mm

### **Substrates**

Screeds required to be fully cured before installation. • Use damp proof membrane (such as 1200 gauge polythene sheet) over ground floor slabs and new concrete bases above ground.

### **Pricing & Ordering**

Prices are based per system pre-designed specifically on a project basis and design allows for a 5% wastage factor. We therefore need only the dimensions of the space to provide all the components required. For larger gyms, small adjoining rooms or irregular shaped areas additional materials will be required, these additional components will require separate calculation and pricing.

Sport & Fitness Flooring  
Wyastone Business Park  
Wyastone Leys  
Monmouth  
NP25 3SR  
T: 01600 887521  
E: [info@sportandfitnessflooring.com](mailto:info@sportandfitnessflooring.com)

### **Lead Times**

6 - 8 Weeks

